

System Requirements Commercial & Digital Printing

OneVision Software AG

Content

Speedflow Check 10.1, Speedflow Check Plus 10.1	2
Speedflow Edit 10.1 (Windows),	2
Speedflow Recompose 10.1	2
Speedflow Edit 10.1 (Macintosh OSX)	2
Speedflow Impose 4.0	3
Speedflow Cockpit 3.5	4
Sicuriq 1.5, Sicuriq Pro 1.5	5

Speedflow Check 10.1, Speedflow Check Plus 10.1

Operating system	Windows XP Professional®, Service Pack 2, 32 Bit Windows Server 2003® Standard Edition Service Pack 2, 32 Bit Windows Server 2003 R2® Standard Edition Service Pack 2, 32 Bit Windows Server 2003 R2® Standard Edition Service Pack 2, 64 Bit Windows Server 2008® Standard Edition Service Pack 2, 32 Bit Windows Server 2008® Standard Edition Service Pack 2, 64 Bit (HASP dongle only)
Processor	Intel Core 2 Duo 2,4 GHz (or faster), 1066 MHz FSB (or faster), AMD Athlon 64 x2 5200+ (or compatible/or faster),
Main memory	4 GB RAM or more recommended on 64 Bit OS 8 GB RAM or more recommended
Hard disk	Fast hard disk, 50 GB available to accommodate installation and virtual memory, RAID 5 or other redundancy recommended, 50 GB free disk space for temporary data (normaly on C:)
Resolution	Support for 24-bit color at 1152 x 864 resolution minimum
CD ROM drive	Required for installation
USB Port	Required for license dongle
Networking	TCP/IP services and active network connection required

Speedflow Edit 10.1 (Windows), Speedflow Recompose 10.1

Operating system	Windows XP Professional®, Service Pack 2, 32 Bit Windows Server 2003 R2® Standard Edition Service Pack 2, 32 Bit Windows Vista Business®, Service Pack 2, 32 Bit
Processor	Intel Core 2 Duo 2,4 GHz (or faster), 1066 MHz FSB (or faster), AMD Athlon 64 x2 5200+ (or compatible/or faster),
Main memory	4 GB RAM or more recommended on 64 Bit OS 8 GB RAM or more recommended
Hard disk	Fast hard disk, 50 GB available to accommodate installation and virtual memory, 50 GB free disk space for temporary data (normaly on C:)
Resolution	Support for 24-bit color at 1152 x 864 resolution minimum
CD ROM drive	Required for installation
USB Port	Required for license dongle
Networking	TCP/IP services and active network connection required

Speedflow Edit 10.1 (Macintosh OSX)

Operating system	Mac OS X 10.4.11 with Java for Mac OS X 10.4 Release 9 Mac OS X 10.5.8 with Java for Mac OS X 10.5 Update 5 Mac OS X 10.6.3 with Java for Mac OS X 10.6 Update 1
Processor	Apple Macintosh with PowerPC G5 1,4 GHz or faster or Intel CPU
Main memory	4 GB RAM or more recommended
Hard disk	Fast hard disk, 30 GB available to accommodate installation and virtual memory
Resolution	Support for 24-bit color at 1152 x 864 resolution minimum
CD ROM drive	Required for installation
USB Port	Required for license dongle
Networking	TCP/IP services and active network connection required

Speedflow Impose 4.0

Operating system	Windows XP Professional®, Service Pack 2, 32 Bit Windows Server 2003 R2® Standard Edition Service Pack 2, 32 Bit Windows Vista Business®, Service Pack 2, 32 Bit
Processor	Intel Pentium 2 GHz (or faster)
Main memory	2 GB RAM or more recommended
Hard disk	Fast hard disk, 30 GB available to accommodate installation, temporary files and virtual memory
Resolution	Support for 24-bit color at 1024 x 768 resolution minimum
CD ROM drive	Required for installation
USB Port	Required for license dongle

Speedflow Cockpit 3.5

Operating system	Windows XP Professional®, Service Pack 2, 32 Bit Windows Server 2003® Standard Edition Service Pack 2, 32 Bit Windows Server 2003 R2® Standard Edition Service Pack 2, 32 Bit
Processor	Intel Pentium IV 2,8 GHz DualCore (or faster), 533 MHz FSB (or faster) recommended AMD Athlon 64 X2 3800+ (or compatible/or faster), recommended
Main memory	2 GB RAM or more recommended
Hard disk	Fast hard disk, 100 GB available to accommodate installation, virtual memory and file storage
Resolution	Support for 24-bit color at 1152 x 864 resolution minimum
CD ROM drive	Required for installation
USB Port	Required for license dongle
Networking	TCP/IP services and active network connection required

License dongles for Speedflow Cockpit and JDFnet require separate USB ports (two dongles are included).

Speedflow Control, Speedflow Interact, and Speedflow AutoImpose – all modules of Speedflow Cockpit – do not require separate license dongles/USB ports.

Speedflow Control 3.5 (Windows), Speedflow Interact 3.5 (Windows)

Operating system	Windows XP Professional®, Service Pack 2, 32 Bit Windows Server 2003® Standard Edition Service Pack 2, 32 Bit Windows Server 2003 R2® Standard Edition Service Pack 2, 32 Bit
Processor	Intel Pentium IV 2.8 GHz or faster, 533 MHz FSB recommended (Hyperthreading currently not supported) AMD Athlon 64 3000+ or compatible/or faster,
Main memory	2 GB RAM or more recommended
Hard disk	Fast hard disk, 30 GB available to accommodate installation, virtual memory and file storage
Resolution	Support for 24-bit color at 1152 x 864 resolution minimum
CD ROM drive	Required for installation
Networking	TCP/IP services and active network connection required

Speedflow Control 3.5 (Macintosh OSX), Speedflow Interact 3.5 (Macintosh OSX)

Operating system	Mac OS X 10.4.11 with Java for Mac OS X 10.4 Release 5 Mac OS X 10.5.8 with Java for Mac OS X 10.5 Update 9 Mac OS X 10.6.3 with Java for Mac OS X 10.6 Update 1
Processor	Apple Macintosh with PowerPC G5 1 GHz or faster Intel based Macintosh systems
Main memory	2 GB RAM or more recommended
Hard disk	Fast hard disk, 30 GB available to accommodate installation and virtual memory
Resolution	Support for 24-bit color at 1152 x 864 resolution minimum
CD ROM drive	Required for installation
Networking	TCP/IP services and active network connection required

Sicuriq 1.5, Sicuriq Pro 1.5

Operating system	Windows 2000 Professional® or Server®, Service Pack 4, Windows XP Professional®, Service Pack 2, 32 Bit, Windows Server 2003® Standard Edition Service Pack 1, 32 Bit
Processor	Intel Core 2 Duo (or compatible) 2 GHz or faster
Main memory	2 GB RAM or more recommended
Hard disk	Fast hard disk, 10 GB available to accommodate installation temporary files and virtual memory
Resolution	Support for 24-bit color at 1152 x 864 resolution minimum
CD ROM drive	Required for installation
USB Port	Required for license dongle
Networking	TCP/IP services and active network connection required

